HYDRAULIC PRUMER











CUTTING UNIT

Also available in a version with twosaw blades with a diameter of 650 mm.

OPTIONAL ITEM WITH PROTECTIVE GRILLE

The Protective Grid prevents pruning material from coming into direct contact with the tractor and compromising operation. The accessory is incorporated into the implement, which makes it possible to change from one tractor to another without having to remove the grid.



PRUNING VERSION WITH SUPPORT WHEELS

All versions of **Raptors TT Pruners** have optional support wheels and protective grid: models **2500 TT, 3000 TT, 3500 TT.**

Implement designedfor exclusive usewith tractor with cab. Use prohibited ontractor without cab.





CHARACTERISTICS	RAPTOR 2500 TT	RAPTOR 3000 TT	RAPTOR 3000 TT	RAPTOR 3500 TT
Maximum top cutting height	3000 mm	4000 mm	3000 mm	4000 mm
Minimum top cutting height	1000 mm	1000 mm	1000 mm	1000 mm
Maximum side cutting height	5000 mm	6800 mm	6000 mm	7000 mm
Minimum side cutting height	400 mm	400 mm	400 mm	400 mm
Saw cutting diameter	2500 mm	3000 mm	3000 mm	3500 mm
Power required	65 cv	90 cv	70 cv	90 cv
Approximate weight with oil	1370 kg	1800 kg	1650 kg	1850 kg



LUMA Implementos Agrícolas Ltda.

Rua 15 de Novembro, 791 - Bairro Santo Antonio / Itapira - SP CEP: 13974-520 - Phone: (19) 3863 3395 vendas6@lumaimplementos.com.br

www.lumaimplementos.com.br

Version 4/March 2025



Luma reserves the right to modify or improvive his products whithout prior announcement.

f lin Luma Implementos